

Portable Electric Vibrator X-MAN/PME





Previous Next Electric portable concrete vibrator. Handles designed to protect the perimeter of the motor against impacts. Cable reinforcement at the motor outlet. 5 times higher resistance casing than required by regulations. Three handles around the motor body and another handle at the rear for handling with short transmissions and vertical work. Anti-abrasion hose with integrated mesh reinforcement and internal strapping. Needle connection reinforced by retreading. Easily removable and adjustable strap. Foam filter and grille at the air inlet. Watertight and shock protected switch. Transmission from 1 to 5 m. Motor very manageable due to its light weight. It has a strap for transport.

Rating: Not Rated Yet

[Ask a question about this product](#)

Description

TECHNICAL SPECIFICATIONS

Power: 2.3KW (3HP)

Vibrating Frequency (VPM): 12000-17000

Rotational Speed (RPM):9500-14000

Hose Length: 5 M

Vibrator Head Dia*Length: 48*355

SPECIFICATIONS High power motor for handling all range of AX vibrator diameters (from 25 to 58 mm) and TDX transmission lengths (from 0.5 m to 6 m).

Reinforced hose for intense use. Handles for easy handling and protection of the motor body. High resistance housing. Air inlet filter. The vibrators have 4 oil-lubricated bearings.